

Series Features



- 120 / 277 VAC Operation
- Maximum Input Rating

120 VAC	60Hz	.028 Amps
277 VAC	60Hz	.01 Amps



- Light-Emitting Diodes - 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output



- Contemporary Design
- Canopy Standard
- Die Cast Aluminum Construction
- Thin-Edge Black Housing
- Brushed Aluminum Stencil Face
- Directional Chevron Snapouts
- Suitable for Damp Location
- UL Listed



Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Increased LED Brightness Level in Emergency Mode



- Sealed Nickel Cadmium Battery
- 10-Year Battery Warranty
- Maintenance-Free

- Test Switch
- Red (Power On) Indicator

Ordering Information

Replacement

DSL Series	2 # Faces	R Letter	A Stencil	B Housing	U Options
DSL - AC DSL - Emer	2	_Red	_Aluminum	_Black	_Universal



Dimensions:

DSL/DSL

Height: 8.50"
Width: 12.81"
Depth: 1.875"

CANOPY ONLY

Height: 4.38"
Width: 5.50"
Depth: 0.625"

Accessories:

38-8 Wire Guard for Single-Face Back Mount Only)

VDS Vandal-Deterrent Shield (for Single-Face Back Mount Only)

