




SERIES FEATURES




| | |
|---|---|
|  | <ul style="list-style-type: none"> ▶ 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) SINGLE FACE 3.6 WATTS DOUBLE FACE 5.8 WATTS |
|  | <ul style="list-style-type: none"> ▶ LIGHT ELIMINATING DIODES ▶ ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS ▶ 100-300 FT. VISIBILITY ▶ 25+ YEARS EXPECTED LIFE |
|  | <ul style="list-style-type: none"> ▶ CONTEMPORARY STYLING ▶ CANOPY STANDARD ON DOUBLE FACE SIGNS ▶ DIE CAST ALUMINUM CONSTRUCTION ▶ THIN EDGE BLACK HOUSING ▶ BRUSHED ALUMINUM STENCIL FACE ▶ DIRECTIONAL CHEVRON SNAP-OUTS ▶ DOWNLIGHT ▶ 2 YEAR PAYBACK ▶ UL LISTED |



DIMENSIONS

| | |
|--------------|--------------------------|
| HEIGHT: 8.4" | CANOPY (WHEN APPLICABLE) |
| WIDTH: 12.0" | HEIGHT: 4.7" |
| DEPTH: 2.3" | WIDTH: 4.7" |
| | DEPTH: 0.8" |

ADDITIONAL EMERGENCY UNIT FEATURES

| | |
|---|---|
|  | <ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ MULTI-RATE, CONTROLLED AUTOMATIC CHARGER CIRCUIT ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY |
|  | <ul style="list-style-type: none"> ▶ SEALED NICKEL CADMIUM BATTERY ▶ 6 VOLT OPERATION ▶ 10 YEAR BATTERY WARRANTY ▶ MAINTENANCE FREE |
|  | <ul style="list-style-type: none"> ▶ TEST SWITCH ▶ RED (POWER ON) INDICATOR |

FACTORY OPTIONS

- CPY CANOPY (SGL FACE SIGNS)
- BZ BUZZER (DXDS ONLY)
- FAI FIRE ALARM INTER-FACE. VISUAL ALARM
- FL FLASHER (DXDS ONLY)
- HI HIGH INTENSITY LED'S
- TP TAMPER PROOF COVER
- RMB RECESSED MOUNT BLACK
- RMW RECESSED MOUNT WHITE
- SL SLAVE
- DL DOWNLIGHT



ORDERING INFORMATION

| | | | | | | |
|--------------------------------------|---|-------------------------------|--|---|---|--|
| DXD SERIES DXD-DIE CAST | S POWER MODE A~AC S~EMERGENCY | 2 # FACES 1 2 | G LETTER COLOR RED GREEN | W STENCIL COLOR WHITE BLACK ALUMINUM * | W HOUSING COLOR WHITE BLACK * ALUMINUM | -FAI OPTIONS FACTORY OPTIONS |
|--------------------------------------|---|-------------------------------|--|---|---|--|

* STANDARD



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT