




Chicago Approved LED Exits



ECXL / ERCXL







Series Features

-  • Maximum Input Rating
120 VAC 24 Watts
277 VAC 24 Watts
-  • White LED 3.7 Watts
• 25 Year Life Expectancy
-  • Open-Face Glass Panel
• Silk Screen Letters
• Ceiling, End, or Back Mount
• Canopy
• Downlight
• 20-Gauge Steel Housing
• White Powder-Coat Finish
• UL Listed
• Chicago Code Approved



Additional Emergency Unit Features

-  • Integrated Solid State System
• Multi-Rate, Controlled, Automatic Charger
• Lock Out (Automatic Battery Connect)
• Brownout Sensitivity
• Dual-Voltage Transformer for 120/277 VAC Operation
-  • White LED 3.7 Watts
• 25 Year Life Expectancy
-  • Sealed Lead Calcium Battery
• 6-Volt Operation
• Maintenance-Free
-  • Test Switch
• Red (Power On) LED Indicator
• UL Listed

Dimensions

ECXL
Height: 16.0"
Width: 12.3"
Depth: 2.8"

ERCXL
Rough in
Opening:
5.8" x 16.8"

Accessories Order Separately

-P12W 12" Pendant Kit, White (Pendant Kits from 12" - 84" available)

Options Add Suffix to Catalog Number

-TP Tamper-Proof Screws

-U Universal Face (Additional Backplate-Double-Face Signs Only)

-UA Universal Arrow (Additional Arrow Knock-out Faceplates)

-SM Side-Mount Battery Pack

For Recessed Mount Models Only:

-SS Stainless Steel Trim Plate

-PA Plenum Construction


Specify Arrow Configuration on all Open-Face Signs

Blank = No Arrow

AR = Arrow Right 

AL = Arrow Left 

DA = Dual Arrow 

ARAL = Arrow Right/
Arrow Left 

(Double-Face Only - 1 Arrow per Face)

Ordering Information

ECXL	2	R	W	W	-UA
Series	# Faces	Letter Color	Panel Color	Housing / Trim Color	Options
ECXL Emer. Surface	1	R - Red	W - White	W - White	
ERCXL Emer. Recessed	2			B - Black PM - Matte Chrome	



Siltron Emergency Systems, Inc.

290 E. Prairie Street
Crystal Lake, IL 60014

