

EM SERIES FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ MULTI-RATE, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING 120VAC 60 Hz 0.20 AMPS 277VAC 60 Hz 0.20 AMPS
	<ul style="list-style-type: none"> ▶ 6 WATT HALOGEN LAMPS
	<ul style="list-style-type: none"> ▶ MAINTENANCE FREE NI-CAD BATTERY ▶ 6 VOLT OPERATION ▶ HEATER OPTION
	<ul style="list-style-type: none"> ▶ INNOVATIVE ARCHITECTURAL DESIGN ▶ DIE-CAST ALUMINUM HOUSING ▶ POLYCARBONATE LENS/MIRRORED REFLECTOR ▶ DECORATIVE PHOTOCELL LED LIGHT ▶ TEST SWITCH/POWER INDICATOR LIGHT ▶ WET LOCATION ▶ ETL LISTED, MEETS UL, NFPA & OSHA



THE EM100 IS GREAT FOR INDOOR OR OUTDOOR APPLICATIONS. A NI-CAD BATTERY ALLOWS FOR USE IN COLD WEATHER CONDITIONS. DECORATIVE PHOTOCELL OPERATED LEDs MAKE THE EM100 TRULY UNIQUE.

UNIT INFORMATION ~ EM100

MODEL NUMBER	VOLT	STD. WATTS PER HOUR			REPLACEMENT BATTERY	
		LAMP WATT	1.5	2		3
EM100	6	6	12	-	-	[1] N65

DIMENSIONS

HEIGHT: 10.5"
WIDTH: 6.5"
DEPTH: 3.75"

FACTORY OPTIONS

-HTR HEATER