

EM12/EM13 EM12/EM13-MR

EXITS / COMBO



EM12/13-MR*



EM12/13*

DIMENSIONS

EM12/EM13	EM12/EM13-MR
HEIGHT: 14.125"	HEIGHT: 14.125"
LENGTH: 12.125"	LENGTH: 12.125"
DEPTH: 4.0"	DEPTH: 4.125"

* DESIGN MAY VARY SLIGHTLY FROM PHOTO.

SERIES FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING <table style="margin-left: 20px; border: none;"> <tr> <td>120VAC</td> <td>60Hz</td> <td>0.02 AMPS</td> </tr> <tr> <td>277 VAC</td> <td>60Hz</td> <td>0.02 AMPS</td> </tr> </table> 	120VAC	60Hz	0.02 AMPS	277 VAC	60Hz	0.02 AMPS
120VAC	60Hz	0.02 AMPS					
277 VAC	60Hz	0.02 AMPS					
	<ul style="list-style-type: none"> ▶ LIGHT-EMITTING DIODES ~ 25+ YEAR LIFE ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS INDIRECT PLACEMENT FOR DIFFUSED LEGEND OUTPUT ▶ EM12/13 PAR-36 TYPE, HIGH INTENSITY TUNGSTEN LAMPS, 6 WATT ▶ EM12/13-MR MR-16 TYPE, HALOGEN LAMPS, 5 WATT 						
	<ul style="list-style-type: none"> ▶ SEALED LEAD ACID BATTERY ▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE 						
	<ul style="list-style-type: none"> ▶ INJECTION MOLDED THERMOPLASTIC HOUSING ▶ SNAP TOGETHER DESIGN FOR FAST INSTALLATION ▶ FULLY ADJUSTABLE LIGHTING HEADS ▶ OFF WHITE FINISH ▶ SINGLE OR DOUBLE FACE CONFIGURATION ▶ REPLACEABLE KNOCK-OUT DIRECTIONAL CHEVRONS ▶ CANOPY FOR SURFACE, END, OR CEILING MOUNT ▶ EM12 - RED ▶ EM13 - GREEN ▶ LED CHARGE RATE INDICATOR ▶ TEST SWITCH ▶ UL LISTED ▶ DAMP LOCATION 						

UNIT INFORMATION

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
		1.5	2	3	4	5	6	7	8	
EM12/13	6	12	~	~	~	~	~	~	~	[1] S65
EM12/13-MR	5	12	~	~	~	~	~	~	~	[1] S65

ILLUMINATION IS RATED TO **87.5%** OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.



SILTRON

PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT