

SERIES FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ FUSED AC INPUT & DC OUTPUT CIRCUIT PROTECTION ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING 120VAC 60 Hz 0.35 AMPS 277VAC 60 Hz 0.15 AMPS
	<ul style="list-style-type: none"> ▶ HIT LAMPS ▶ PAR-36 SEALED BEAM LAMPS <div style="display: flex; align-items: center; justify-content: space-between;"> <div style="font-size: small; text-align: center;">S L T A M P</div> <div>▶ SEE UNIT INFORMATION</div> </div>
	<ul style="list-style-type: none"> ▶ SEALED LEAD ACID BATTERY/SEALED NI-CAD ▶ 6 OR 12 VOLT OPERATION ▶ MAINTENANCE FREE
	<ul style="list-style-type: none"> ▶ RUGGED 20 GAUGE STEEL HOUSING ▶ TOP END BATTERY ACCESS ▶ FULL LENGTH PIANO HINGE ▶ KEY HOLE MOUNTING ▶ BEIGE POWDER COAT FINISH STANDARD ▶ WOODGRAIN PANEL DESIGN ▶ TEST SWITCH ▶ AMMETER ▶ RED (POWER ON) & GREEN (TRICKLE CHARGE) LED INDICATORS ▶ UL LISTED ▶ NEW YORK CITY APPROVED/CALENDAR #32110



SHOWN IN STANDARD BEIGE FINISH WITH WOODGRAIN PANEL

THE EM20 SERIES IS A HIGH-END COMMERCIAL UNIT, OFFERING THE APPEALING BLEND OF DURABLE STEEL CONSTRUCTION WITH AN ATTRACTIVE, NEAT APPEARANCE. ENHANCED UNIT STATUS INFORMATION IS PROVIDED THROUGH INDICATOR AND METER DISPLAYS.

DIMENSIONS

HEIGHT: 13.5"
WIDTH: 13.5"
DEPTH: 4.75"

FACTORY OPTIONS

- CP CORD & PLUG FOR 120 VAC INPUT
- NWG LESS WOODGRAIN
- OW DESIGNER OFFWHITE FINISH
- GY INDUSTRIAL GREY FINISH
- QC QUIK CHEK REMOTE TEST & TIME DELAY
- TD TIME DELAY ADJUSTS 1-60 MIN.
- W WHITE FINISH
- V VOLTMETER *
- ** SPECIAL LAMP WATTAGE

*IN PLACE OF AMMETER

UNIT INFORMATION

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
		1.5	2	3	4	5	6	7	8	
EM20	8	18	14	9	7	~	~	~	~	[1] S68
EM21	8	45	36	20	15	12	10	9	8	[2] S68
EM22	8	64	50	32	24	19	16	14	12	[2] S610-SL
EM23	8	100	75	50	38	30	25	21	18	[1] S636
EM24 †	12	32	24	16	12	10	8	7	6	[1] S610-SL
EM25 †	12	45	36	20	15	12	10	9	8	[2] S68
EM26 †	12	64	50	32	24	19	16	14	12	[2] S610-SL
EM27 †*	12	36	27	18	14	11	9	8	7	[2] S68
EM28 †*	12	60	45	30	23	18	15	13	11	[2] S610-SL
EM29 †*	12	100	75	50	38	30	25	21	18	[1] S1215
EM24-N7 †	12	25	18	14	9	-	-	-	-	[1] N67F
EM28-N7 †*	12	50	36	24	18	14	12	10	9	[2] N67F

† CHICAGO CODE APPROVED

* 12 VOLT DC OUTPUT

ILLUMINATION IS RATED TO **87.5%** OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT