



DESIGNED FOR USE IN AREAS WHERE UNIT SIZE AND COST ARE PREMIUM CONSIDERATIONS, THE POLYCARBONATE HOUSING MAKES IT IDEAL FOR LIGHT COMMERCIAL ENVIRONMENTS.

DIMENSIONS

HEIGHT: 7.15"
 WIDTH: 11.25"
 DEPTH: 6.95"

SERIES FEATURES

- ▶ INTEGRATED SOLID STATE SYSTEM
 - ▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER
 - ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)
 - ▶ LOW VOLTAGE BATTERY CUTOFF
 - ▶ BROWNOUT SENSITIVITY
 - ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION
 - ▶ MAXIMUM INPUT RATING
 120VAC 60 Hz 0.20 AMPS
 277VAC 60 Hz 0.20 AMPS
-
- ▶ HIGH INTENSITY TUNGSTEN LAMPS S L T A M D P ▶ 6 VOLT ~ 6 WATT
-
- ▶ SEALED LEAD ACID BATTERY
 - ▶ 6 VOLT OPERATION
 - ▶ MAINTENANCE FREE
-
- ▶ COMPACT DESIGN
 - ▶ FLAME RETARDANT NORYL 190® HOUSING
 - ▶ UNIVERSAL MOUNT, GALVANIZED STEEL BACKPLATE
 - ▶ HIGH IMPACT, MIST WHITE FINISH
 - ▶ RED (POWER ON) LED INDICATOR
 - ▶ TEST SWITCH
 - ▶ UL LISTED
 - ▶ WALL OR CEILING MOUNT
 - ▶ DAMP LOCATION LISTED

UNIT INFORMATION

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
		1.5	2	3	4	5	6	7	8	
EM40L	6	12	9	6	~	~	~	~	~	[1] S65

ILLUMINATION IS RATED TO **87.5%** OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.

