





SERIES FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING 120VAC 60 Hz 0.20 APMS 277VAC 60 Hz 0.20 APMS
	<ul style="list-style-type: none"> ▶ HIGH INTENSITY TUNGSTEN LAMPS <div style="display: flex; align-items: center; margin-left: 100px;"> <div style="text-align: center; margin-right: 10px;"> <p>S L A M P</p> </div> <p>▶ 6 VOLT ~ 6 WATT</p> </div>
	<ul style="list-style-type: none"> ▶ SEALED LEAD ACID BATTERY ▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE
	<ul style="list-style-type: none"> ▶ COMPACT DESIGN ▶ INJECTION MOLDED THERMOPLASTIC HOUSING ▶ HIGH IMPACT, OFF WHITE FINISH ▶ RED (POWER ON) LED INDICATOR ▶ TEST SWITCH ▶ DAMP LOCATION ▶ ETL TESTED



DESIGNED FOR USE IN AREAS WHERE UNIT SIZE AND COST ARE PREMIUM CONSIDERATIONS, THE EM41 THERMOPLASTIC HOUSING MAKES IT IDEAL FOR LIGHT COMMERCIAL ENVIRONMENT.

UNIT INFORMATION

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
		1.5	2	3	4	5	6	7	8	
EM41	6	12	9	6	~	~	~	~	~	(1) S65

ILLUMINATION IS RATED TO 87% OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION

DIMENSIONS

HEIGHT: 5.0"
WIDTH: 16"
DEPTH: 4.5"