

**SERIES FEATURES**

	<ul style="list-style-type: none"> <li>▶ INTEGRATED SOLID STATE SYSTEM</li> <li>▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER</li> <li>▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)</li> <li>▶ LOW VOLTAGE BATTERY CUTOFF</li> <li>▶ BROWNOUT SENSITIVITY</li> <li>▶ FUSED AC INPUT &amp; DC OUTPUT CIRCUIT PROTECTION</li> <li>▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION</li> <li>▶ MAXIMUM INPUT RATING 120VAC 60 Hz 0.35 AMPS 277VAC 60 Hz 0.15 AMPS</li> </ul>				
	<ul style="list-style-type: none"> <li>▶ PAR-36 SEALED BEAM LAMPS</li> </ul>				
	<table border="0"> <tr> <td style="text-align: center;">S L A M P</td> <td>▶ 6 VOLT ~ 25 WATT</td> </tr> <tr> <td></td> <td>▶ 12 VOLT ~ 25 WATT</td> </tr> </table>	S L A M P	▶ 6 VOLT ~ 25 WATT		▶ 12 VOLT ~ 25 WATT
S L A M P	▶ 6 VOLT ~ 25 WATT				
	▶ 12 VOLT ~ 25 WATT				
	<ul style="list-style-type: none"> <li>▶ SEALED LEAD ACID BATTERY [S]</li> <li>▶ REFILLABLE LEAD ACID BATTERY [L]</li> <li>▶ 6, 12, OR 24 VOLT OPERATION</li> </ul>				
	<ul style="list-style-type: none"> <li>▶ RUGGED 20 GAUGE STEEL HOUSING</li> <li>▶ FRONT END BATTERY ACCESS</li> <li>▶ KEYHOLE MOUNTING WITH INTEGRAL SHELF</li> <li>▶ TWO-TONE POWDER COAT FINISH (BEIGE &amp; COCOA) STANDARD</li> <li>▶ TEST SWITCH</li> <li>▶ AMMETER</li> <li>▶ MODULAR CONTROL CHASSIS</li> <li>▶ RED (POWER ON) &amp; GREEN (TRICKLE CHARGE) INDICATORS</li> <li>▶ UL LISTED</li> <li>▶ NEW YORK CITY APPROVED/CALENDAR #38236</li> </ul>				



SHOWN IN STANDARD TWO TONE BEIGE & COCOA FINISH

STREAMLINED PRODUCT DESIGN MAKES THE EM70 SERIES THE PERFECT CHOICE FOR LIGHT INDUSTRIAL APPLICATIONS WHERE AESTHETICS ARE OF PRINCIPAL CONSIDERATION. AVAILABLE WITH SEALED OR REFILLABLE BATTERIES FOR USE IN A WIDE TEMPERATURE RANGE.

**DIMENSIONS**

HEIGHT: 17.25"  
WIDTH: 15.75"  
DEPTH: 7.50"

**UNIT INFORMATION**

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR				REPLACEMENT BATTERY
		1.5	2	4	8	
EM70 †	25	64	50	24	12	[2] S610SL
EM71 †	25	100	75	38	18	[1] S636
EM72 †	25	120	90	45	23	[1] S650
EM75 †*	25	60	45	23	11	[2] S610SL
EM76 †*	25	100	75	38	18	[1] S1215
EM77 †*	25	120	90	45	23	[1] S1220
EM78 †*	25	200	150	76	36	[2] S636
EM79-1 **	7	110	84	42	21	[4] S610SL
EM79-2 **	7	220	165	83	42	[2] S1215
EM73 †	25	120	90	45	23	[1] L640

† CHICAGO CODE APPROVED

\* 12 VOLT DC OUTPUT

\*\* 24 VOLT DC OUTPUT

ILLUMINATION IS RATED TO **87.5%** OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.

**FACTORY OPTIONS**

- CP CORD & PLUG FOR 120 VAC INPUT
- BG ALL BEIGE FINISH
- OW OFFWHITE FINISH
- GY INDUSTRIAL GREY FINISH
- TD TIME DELAY AJUSTS 1-60 MIN.
- V VOLTMETER \*
- \*\* SPECIAL LAMP WATTAGE
- H HALOGEN LAMPS
- QC QUIK CHEK REMOTE TEST & TIME DELAY

\*IN PLACE OF AMMETER



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT