






LXN SERIES FEATURES

	▶ NO ELECTRICAL POWER REQUIRED
	▶ CERTIFIED VIEWING DISTANCE OF 75 FEET ▶ UNFILTERED FLOURESCENT, METAL HALIDE OR MERCURY VAPOR ILLUMINATION MUST BE PRESENT ON THE SIGN FACE
	▶ NO BATTERY REQUIRED
	▶ 25 YEAR EXPECTED LIFE
	▶ NO INTERNAL OR EXTERNAL WIRING REQUIRED ▶ EXPLOSION PROOF/WATERPROOF/CORROSION, MOLD AND VAPOR PROOF ▶ NON-TOXIC/NON-RADIOACTIVE ▶ UV-STABLE ▶ SURFACE, CEILING OR SIDE MOUNT ▶ FIELD INSTALLED DIRECTIONAL CHEVRONS ▶ HEAVY-DUTY ALUMINUM FRAME ▶ UL 924 LISTED ▶ ENERGY STAR LISTED



THE LXN IS A SELF SUFFICIENT EXIT SIGN THAT REQUIRES NO ENERGY, WIRING, OR BATTERIES. THIS SIGN IS GREAT FOR APPLICATIONS WHERE COST TO OPERATE IS A PREMIUM CONCERN.

DIMENSIONS

Height: 9.25"
Width: 15.75"

OPTIONS:

-NF No FRAME


ORDERING INFORMATION

SERIES	# OF FACES	LETTER COLOR	UNIVERSAL MOUNTING
LXN	1 2	RED GREEN	-U



EXAMPLE: LXN1R-U

PL SERIES FEATURES

	▶ REQUIRES NO ELECTRICAL SUPPLY
	▶ PHOTO-LUMINOUS PANEL WITHIN DIE CAST ALUMINUM HOUSING ▶ INITIAL BRIGHTNESS - 1.5 FOOT CANDLES ▶ 6-HOUR PANEL ILLUMINATION ▶ RECHARGEABLE TO FULL CAPACITY WITH 8 MINUTES EXPOSURE TO 50-60 FC ILLUMINATION
	▶ REQUIRES NO BATTERY
	▶ 20 YEAR EXPECTED LIFE
	▶ DIE CAST ALUMINUM HOUSING WITH BRUSHED ALUMINUM STENCIL FACE AND BLACK HOUSING ▶ ALL WHITE OR ALL BLACK FINISH AVAILABLE ▶ DIRECTIONAL CHEVRON/ARROW KNOCKOUTS ▶ SINGLE FACE, BACK MOUNT ONLY ▶ LESS THAN 1" DEEP ▶ NO INTERNAL OR EXTERNAL WIRING REQUIRED ▶ EXPLOSION PROOF/WATERPROOF/CORROSION, MOLD AND VAPOR PROOF ▶ FOR INTEGRATED USE IN FLOOR PROXIMITY EGRESS MARKING SYSTEMS

PL



DIMENSIONS

Height: 8.5"
Width: 12.0"
Depth: 0.925"

EXAMPLE: 1PLGAB

ORDERING INFORMATION

# FACES	SERIES	LETTER COLOR	STENCIL COLOR	HOUSING COLOR
1	PL	G GREEN	A WHITE BLACK ALUMINUM	B WHITE BLACK



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT