








SERIES FEATURES

	NEMA APPLICATIONS
	▶ ALL UNITS SATISFY THE REQUIREMENTS OF NEMA 1, 2, 3, 3R, 4, & 4X ENCLOSURES
	▶ CHOICE OF LIGHT SOURCE INCANDESCENT 2,000 HOURS FLUORESCENT 10,000 HOURS LED (INDIRECT VIEW) 25+ YEARS LED (DIRECT VIEW) 25+ YEARS
	▶ DESIGNED FOR USE IN CORROSIVE, DIRTY, OR DAMP ENVIRONMENTS ▶ BACK MOUNT STANDARD ▶ UNIVERSAL STENCIL FACE ▶ DIRECTIONAL CHEVRON SNAPOUTS ▶ INDUSTRIAL GRAY FIBERGLASS HOUSING ▶ MEETS OR EXCEEDS UL924

ADDITIONAL EMERGENCY UNIT FEATURES

	▶ INTEGRATED SOLID STATE SYSTEM ▶ CONSTANT CURRENT, AUTOMATIC CHARGER ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ AC LOCKOUT (LINE LATCHING)
	▶ MOUNTED LIGHTING HEADS AVAILABLE: CHOICE OF 8 WATT INCANDESCENT OR HALOGEN SEALED BEAM LAMPS ▶ [2] 6V, 6W HIT LAMPS (NXIS, NXFS, & NXLS)
	▶ SEALED BATTERY ▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE
	▶ TEST SWITCH ▶ RED (POWER ON & CHARGE) INDICATOR

ORDERING INFORMATION

SERIES NX	LAMP TYPE F F=FLUOR. I=INCAN L=LED (DIFFUSED) D=LED (DIRECT)	TYPE S S= EMER A= AC	LETTER COLOR 1R 1R=R ED 1G=G REEN*	OPTIONS -2H
---------------------	--	--------------------------------------	--	-----------------------



DIMENSIONS

WITHOUT HEADS	WITH HEADS
HEIGHT: 9.5"	HEIGHT: 9.5"
WIDTH: 11.5"	WIDTH: 21.6"
DEPTH: 5.5"	DEPTH: 5.5"

FACTORY OPTIONS

- 277** 277 VAC INPUT
- MK** MOUNTING KIT FOR END OR CEILING MOUNT
- QC** QUIK CHEK REMOTE TEST & TIME DELAY (FOR EMERGENCY SIGNS ONLY)
- HTR** HEATER

SERIES	LIGHT SOURCE	STANDARD VOLTAGE	MAX INPUT WATTS (120VAC)		MAX INPUT WATTS (277VAC)		ILLUMINATION TIME (HRS.)		REPLACEMENT BATTERY	
			LESS HDS.	WITH HDS.	LESS HDS.	WITH HDS.	LESS HDS.	WITH HDS.	LESS HDS.	WITH HDS.
AC ONLY										
NXIA	INCANDESCENT	120V*	24W	N/A	30W	N/A	N/A	N/A	N/A	N/A
NXFA	FLUORESCENT	120V*	20W	N/A	30W	N/A	N/A	N/A	N/A	N/A
NXLA	LED (INDIRECT)	120/277V	1.7W	N/A	1.7W	N/A	N/A	N/A	N/A	N/A
NXDA	LED (DIRECT)	120/277V	3.6W	N/A	3.6W	N/A	N/A	N/A	N/A	N/A
EMERGENCY										
NXIS	INCANDESCENT	120V*	26W	30W	26W	30W	1.5	1.5	S65	S610SL
NXFS	FLUORESCENT	120V*	21W	30W	25W	30W	1.5	1.5	S65	S610SL
NXLS	LED (INDIRECT)	120/277V	1.7W	11W	1.7W	11W	3.0	1.5	N71	S610SL
NXDS	LED (DIRECT)	120/277V	6.8W	6.8W	6.8W	6.8W	3.5	1.5	N51	S68

* FOR 277VAC - SEE OPTIONS

