








SERIES FEATURES

	<ul style="list-style-type: none"> ▶ 120/277 VAC OPERATION ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) STANDARD 1.7 WATTS
	<ul style="list-style-type: none"> ▶ LIGHT EMITTING DIODES ~ 25+ YEAR LIFE ▶ ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS ▶ INDIRECT PLACEMENT FOR DIFFUSED LEGEND OUTPUT
	<ul style="list-style-type: none"> ▶ CEILING, END, OR BACK MOUNT ▶ CANOPY ▶ UNIVERSAL STENCIL ▶ DIRECTIONAL CHEVRON SNAPOUTS ▶ WHITE FINISH ▶ EASY INSTALLATION ▶ ETL LISTED OR UL LISTED ▶ FLAME RETARDANT, HIGH IMPACT, THERMOPLASTIC HOUSING ▶ DAMP LOCATION

*



ADDITIONAL EMERGENCY UNIT FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ CONSTANT CURRENT, CONTROLLED AUTOMATIC CHARGER CIRCUIT ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY
	<ul style="list-style-type: none"> ▶ INCREASED LED BRIGHTNESS LEVEL IN EMERGENCY MODE
	<ul style="list-style-type: none"> ▶ SEALED NICKEL CADMIUM BATTERY ▶ 5 YEAR SHELF LIFE ▶ 10 YEAR BATTERY WARRANTY ▶ MAINTENANCE FREE
	<ul style="list-style-type: none"> ▶ TEST SWITCH ▶ LED (POWER ON) INDICATOR



FACTORY OPTIONS

- SALIDA
- 2H** 2 HEADS
- RMT*** REMOTE CAPABILITY

*PXLS-2H ONLY.

* DESIGN MAY VARY FROM PHOTO SLIGHTLY



ORDERING INFORMATION

PXL SERIES PXLA ~ AC PXLS ~ EMER.	2 # FACES 2	R LETTER COLOR <u>R</u> ED <u>G</u> REEN	W STENCIL COLOR <u>W</u> HITE	W HOUSING COLOR <u>W</u> HITE	U UNIVERSAL SINGLE OR DOUBLE FACE
---	------------------------------	--	--	--	---



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT