



CONSTRUCTED OF INDUSTRIAL GRADE FIBERGLASS, THE SE SERIES IS THE ONLY CHOICE FOR SEVERE AND CORROSIVE APPLICATIONS. ALL UNITS SATISFY THE REQUIREMENTS OF NEMA 1,2,3,3R,4,4X ENVIRONMENTS.

DIMENSIONS

- HEIGHT: 16.9" SE20
- WIDTH: 9.4" SE36
- DEPTH: 5.5"

- HEIGHT: 18.8" SE50
- WIDTH: 11.4" SE75
- DEPTH: 5.5"

- HEIGHT: 20.6" SE100
- WIDTH: 13.5" SE125
- DEPTH: 7.0"

- HEIGHT: 20.6" SE200
- WIDTH: 13.5" SE250
- DEPTH: 7.0"

FACTORY OPTIONS

- QC** QUIK CHEK REMOTE TEST & TIME DELAY
- TD** TIME DELAY
- **** SPECIAL WATTAGE LAMPS
- TH** THERMAL HEATER
- NC** NICKEL CADMIUM BATTERY
- H** HALOGEN LAMPS
- FSH** FOOD SAFE HEADS

SERIES FEATURES

NEMA APPLICATIONS

- ▶ ALL UNITS SATISFY THE REQUIREMENTS OF NEMA 1, 2, 3, 3R, 4, 4X, 12 & 13 ENCLOSURES

- ▶ INTEGRATED SOLID STATE SYSTEM
- ▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER
- ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)
- ▶ LOW VOLTAGE BATTERY CUTOFF
- ▶ BROWNOUT SENSITIVITY
- ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION
- ▶ MAXIMUM INPUT RATING
120VAC 60 Hz 0.35 AMPS
277VAC 60 Hz 0.15 AMPS

▶ PAR-36 SEALED BEAM LAMPS	S L A M P	▶ 6 VOLT ~ 8 WATT 12 VOLT ~ 12 WATT
----------------------------	-----------------------	--

- ▶ SEALED LEAD ACID BATTERY
- ▶ 6 OR 12 VOLT OPERATION
- ▶ MAINTENANCE FREE

- ▶ NEMA RATED FOR CORROSIVE, DIRTY, OR DAMP ENVIRONMENTS
- ▶ INDUSTRIAL GRAY FIBERGLASS HOUSING
- ▶ POLYCARBONATE LAMP ENCLOSURES
- ▶ HINGED FRONT PANEL WITH LOCK HASP
- ▶ EASY BATTERY ACCESS
- ▶ SIDE MOUNTED TEST SWITCH
- ▶ RED (POWER ON & CHARGE) INDICATOR
- ▶ MEETS OR EXCEEDS UL 924

UNIT INFORMATION

MODEL NUMBER	BATT VLTG	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
			1.5	2	3	4	5	6	7	8	
SE20	6	8	18	14	9	7	~	~	~	~	[1] S68
SE36	6	8	32	24	16	12	10	8	7	6	[1] S610-SL
SE50	6	8	45	36	20	15	12	10	9	8	[2] S68
SE75	6	8	64	50	32	24	19	16	14	12	[2] S610-SL
SE100	6	8	100	75	50	38	30	25	21	18	[1] S636
SE200	6	8	200	150	100	75	60	50	43	38	[2] S636
SE50-12	12	12	36	27	18	14	11	9	8	7	[2] S68
SE75-12	12	12	60	45	30	23	18	15	13	11	[2] S610-SL
SE100-12	12	12	100	75	50	38	30	25	21	18	[1] S1215
SE125-12	12	12	120	90	60	45	36	30	26	23	[1] S1220
SE200-12	12	12	200	150	100	75	60	50	43	38	[2] S636
SE250-12	12	12	250	200	125	100	90	80	73	68	[2] S1224

ILLUMINATION IS RATED TO **87.5%** OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.



ORDERING INFORMATION

SE SERIES	20 UNIT SIZE	-QC OPTIONS
--------------	-----------------	----------------

