



THE SEXP SERIES IS DESIGNED FOR USE IN CLASS I, DIVISION I HAZARDOUS AREAS. LIGHTING FIXTURES AND EXIT FIXTURES ARE AVAILABLE FOR MOUNTING DIRECTLY TO THE HOUSING OR CAN BE REMOTELY MOUNTED.

DIMENSIONS	
HEIGHT:	12.0"
WIDTH:	15.0"
DEPTH:	8.8"

UNIT INFORMATION ~ SEXP

MODEL NUMBER	WATTS PER HOUR				REPLACEMENT BATTERY
	VOLT	1.5	2	3	
SE68XP	6	25	18	10	[1] N67
SE128XP	12	50	37	20	[2] N67

SEXP SERIES FEATURES

NEC ENVIRONMENT RATINGS

- ▶ MEETS OR EXCEEDS UL SPECIFICATIONS FOR USE IN THE FOLLOWING AREAS
 - CLASS I, DIVISION I, GROUPS C & D
 - CLASS II, DIVISION I, GROUPS E, F, & G
 - CLASS III
- ▶ INTEGRATED SOLID STATE SYSTEM
- ▶ CONTROLLED, AUTOMATIC CHARGER
- ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION

- ▶ PAR-36 SEALED BEAMS S L T A M D P ▶ SEE UNIT INFORMATION

- ▶ SEALED NICKEL CADMIUM BATTERY (N)
- ▶ 6 OR 12 VOLT OPERATION
- ▶ MAINTENANCE FREE

- ▶ COMPLETELY SELF-CONTAINED OPERATION
- ▶ HEAVY CAST, COPPER-FREE ALUMINUM HOUSING
- ▶ SEALED TEST SWITCH
- ▶ POWER ON INDICATOR
- ▶ UL LISTED ENCLOSURES AND FIXTURES

6-VOLT HAZARDOUS AREA EMERGENCY LIGHTING POWER UNITS COMPLETE WITH BATTERIES AND CHARGERS



- SINGLE-HEAD UNIT WITH 20-WATT HALOGEN LAMP



- SINGLE EXIT FIXTURE WITH 20-WATT HALOGEN LAMP



- DOUBLE-HEAD UNIT WITH 10-WATT HALOGEN LAMP
- DOUBLE-HEAD UNIT WITH 20-WATT HALOGEN LAMP



- SINGLE-HEAD AND SINGLE EXIT WITH 10-WATT HALOGEN LAMP
- SINGLE-HEAD AND SINGLE EXIT WITH 20-WATT HALOGEN LAMP

FOR POWER UNITS WITH LIGHTING HEADS AND/OR EXIT FIXTURES MOUNTED DIRECTLY TO THE HOUSING, CHOOSE FROM THE MODELS LISTED ABOVE. THESE UNITS ARE SUPPLIED WITH A SWIVEL ELBOW FOR EACH LIGHTING FIXTURE. CONDUIT IS TO BE SUPPLIED BY THE INSTALLER.