






SERIES FEATURES

	▶ REQUIRES NO ELECTRICAL SUPPLY
	▶ INTERNALLY ILLUMINATED GLASS TUBES COATED WITH ZINC PHOSPHOR AND TRITIUM GAS ▶ INITIAL BRIGHTNESS - 0.15 FOOT LAMBERTS (10 YR.) 0.18 FOOT LAMBERTS (15 YR.) 0.25 FOOT LAMBERTS (20 YR.) ▶ END OF LIFE BRIGHTNESS EXCEEDS MINIMUM CODE REQUIREMENT OF .06 FOOT LAMBERTS
	▶ REQUIRES NO BATTERY SUPPLY
	▶ 10, 15, OR 20 YEAR ILLUMINATION
	▶ NO INTERNAL OR EXTERNAL WIRING REQUIRED ▶ COMPLETELY SEALED ▶ EXPLOSION PROOF ▶ WATER PROOF ▶ CORROSION, MOLD, AND VAPOR PROOF ▶ OPERATING RANGE: -60° ~ +180°F ▶ HIGH IMPACT, ABS FIRE RETARDANT CASE ▶ LEXAN® COVER ▶ CEILING, END, OR BACK MOUNT ▶ UNIVERSAL ARROW CONFIGURATION ▶ MIST WHITE FINISH ▶ COMPLIES WITH NFPA LIFE SAFETY CODE, NRC, OSHA, AND COUNCIL OF AMERICAN BUILDING OFFICIALS ▶ UL LISTED



DIMENSIONS

HEIGHT: 8.2"
WIDTH: 12.6"
DEPTH/SINGLE: 1.0"
DEPTH/DOUBLE: 2.1"

FACTORY OPTIONS

- AF ALUMINUM FRAME
- IF INSTITUTIONAL FRAME
- R RECESSED MOUNT
- PG VANDAL SHIELD
- P PENDANT MOUNT



ORDERING INFORMATION

SX SERIES	2 # FACES 1 2	R STENCIL COLOR R ED G REEN B LACK	10 SIGN LIFE 10 YEARS 15 YEARS 20 YEARS	W HOUSING COLOR W HITE * B LACK G RAY	-R OPTIONS FACTORY OPTIONS
---------------------	-------------------------------	---	--	--	--

* STANDARD



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT