



### DIMENSIONS

HEIGHT: 8.5"  
 WIDTH: 13.0"  
 DEPTH: 3.25"

### FACTORY OPTIONS

- DMP** DAMP LOCATION LISTING
- HTR** HEATER
- BZ** BUZZER (VXDS ONLY)
- FAI** FIRE ALARM INTERFACE (VXDA, VXDS ONLY)
- FL** FLASHER (VXDS ONLY)
- HI** HIGH INTENSITY LEDs
- DL** DOWNLIGHT LED (VXDA, VXDS ONLY)
- DS** DOUBLE LED STRIPS (VXLA, VXLS ONLY)
- 2C** (2) INDEPENDENT AC CIRCUITS

### SERIES FEATURES



- ▶ 120/277 VAC INPUT
- ▶ LIGHT EMITTING DIODES
- ▶ ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS
- ▶ DIRECTLY VIEWED LEDs HAVE 100-300 FT. VISIBILITY
- ▶ 25+ YEARS LIFE (NO RELAMPING)



- ▶ RUGGED 16 GAUGE HOUSING
- ▶ POLYCARBONATE FACE SHIELD
- ▶ TAMPER PROOF SCREWS
- ▶ CANOPY FACTORY ATTACHED (SPECIFY LOCATION)
- ▶ MEETS OR EXCEEDS UL STANDARDS
- ▶ WHITE POWDER COAT FINISH

### ADDITIONAL EMERGENCY UNIT FEATURES



- ▶ INTEGRATED SOLID STATE SYSTEM
- ▶ CONSTANT CURRENT, AUTOMATIC CHARGER CIRCUIT
- ▶ LOW VOLTAGE BATTERY CUTOFF
- ▶ BROWNOUT SENSITIVITY
- ▶ AC LOCKOUT (LINE LATCHING)



- ▶ INCREASED ILLUMINATION DURING POWER FAILURE
- ▶ TEST SWITCH
- ▶ POWER ON INDICATOR LED LAMP



- ▶ SEALED NICKEL CADMIUM BATTERY
- ▶ 5 YEAR SHELF LIFE
- ▶ 10 YEAR BATTERY WARRANTY
- ▶ MAINTENANCE FREE

DIRECT VIEW LED FEATURES			DIFFUSED LED FEATURES	
MAXIMUM INPUT RATING (120 OR 277 VAC):			MAXIMUM INPUT RATING (120 OR 277 VAC):	
AC	SINGLE FACE	3.6 WATTS	STANDARD	1.7 WATTS
	DOUBLE FACE	5.6 WATTS	DS OPTION	3.5 WATTS
EMERGENCY	SINGLE FACE	6.8 WATTS	3+ HOURS ILLUMINATION IN EMERGENCY MODE	
	DOUBLE FACE	8.0 WATTS		
3+ HOURS ILLUMINATION IN EMERGENCY MODE (SINGLE)				
1.5+ HOURS ILLUMINATION IN EMERGENCY MODE (DOUBLE)				

### ORDERING INFORMATION

SERIES	LAMP TYPE	TYPE	LETTER COLOR
VX	L	S	1R
	L - DIFFUSED LED D - DIRECT VIEW LED	A - AC S - EMER	1R - RED 1G - GREEN

